

ZK521ST

Eco-friendly compact high brightness 4K UHD short throw laser projector



- **True 4K UHD resolution and laser technology - 5000 lumens, HDR and HLG compatible**
- **Small form factor for easy installation - Short throw lens, 360-degree and portrait projection**
- **Optoma Management Suite (OMSC)™ - Remotely manage and control your device with real-time monitoring, and scheduling, helping to reduce downtime, streamline operations, and cut operating costs.**
- **Optoma Smart Control App - Streamlines device management allowing you to command, control and make image corrections all from your mobile device.**



The ZK521ST is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 5000-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

Compatible with Optoma Management Suite (OMSC)™ and Optoma's latest Smart Control App, control and manage your devices remotely with ease.

Specifications

UPC: 796435 44 856 1, EAN: 5055387669697, Colour: White



Display/image	
Display technology	DLP®
Resolution	UHD (3840x2160)
Brightness	5,000 lumens
Contrast ratio	3,000,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9, 16:10, 21:9, 32:9
Keystone correction - horizontal	15°
Keystone correction - vertical	15°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 150Khz
Vertical scan rate	24 ~ 240Hz
Uniformity	75%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.79:1
Projection distance (m)	0.33m - 3.3m
Zoom type	Fixed
Focal length (mm)	11.6mm
Lens shift	Vertical -106 ~ 127%
Native offset	106%
Lens shift	Yes - see product downloads for more information
Connectivity	
Connections	Inputs 2 x HDMI 2.0 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x USB-A wireless, 1 x RJ45, 1 x 12V trigger, 1 x RS232, 1 x 3D sync
General	
Noise level (min)	29dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries BT Dongle Basic user manual
Networking	
LAN	Yes
Power	
Power supply	External power supply, 100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	147W
Power consumption (max)	196W
Weight and dimensions	
Dimensions (W x D x H) mm	274 x 216 x 114
Gross weight	4.5 kg
Net weight	3 kg